Rain Garden Design & Construction Worksheet Todd County

Project Goals

1. Drainage Goals: 1 to 2.5 inches of rain in 24 hour period

Engineering Design Steps

Step 1: Determine Drainage Area

What areas do you want to capture water from?

Drainage Area	Area in sq ft
Diamago / nou	Alea III sq II
☐ Gutter/Roof – area 1	
☐ Gutter/Roof – area 2	
☐ Driveway (slopes to garden)	
│ │	
_ rtaintay, pade	
☐ Low spot	
│ │	
cam	
	9 30 30 40 40 40 40 40 40 40 40 40 40 40 40 40
☐ Base of hill	
	*
│ │	
= strock (constant originator)	
☐ Other:	
TOTAL sq ft DRAINAGE	
TOTAL 34 IL DRAINAGE	

Step 2: Determine Location

Does location meets following criteria?

\neg	Garden	af	least	10'	from	house
	Caluell	aı	10001	10	HUH	HOUSE

- ☐ Garden is not over utilities
- ☐ Garden is not over septic system
- ☐ Slope < 12% (12' rise over 100' distance)
- ☐ Called Gopher 1 for locates (651-454-0002)

Step 3: Analyze Soil and Determine Amendments A. Soil texture

Test more than one area of garden. Take soil sample 6"-12" below bottom of garden.

Use soil texture worksheet to determine texture, or have soil test done.

Your soil	Class	texture		Recommended amendments
Α	Sand	Sandy		npost helpful, but not required
В	Silt loam Loam		Add 1-2" compost	
С	Sandy clay loam		m Add 2-4" compost	
D	Claye	у	Add	d 2-4" compost

B. Infiltration test results - optional for sandy soils

Use infiltration rate worksheet to determine infiltration rate. Record rates:

Hours to infiltrate 6" water	Recommended amendments
☐ 4 hours	Compost helpful but not required
□ 8 hours	Till in 1-2" compost
□ 12	Till in 2-4" compost
□ 24	Till in 2-4" compost
□ 48	Till in 3-6" compost

C. Soil compaction - optional

Conduct wire flag test (poke wire flag in ground)

☐ Easily penetrates 6"-8" or more ☐ Compacted, difficult to insert
_ Compacted, difficult to insert

Step 4: Determine Garden Depth and Size

Depth: Gardens with clay soils will be shallower since they infiltrate slowly and rain gardens should infiltrate within 24-48 hours.

Soil Type	Typical Depth
Type A – sandy soils	☐ 9"-12" depth
Type B – silty loam Type C – loamy soils	☐ 6"-9" depth
Type D – clay soils	☐ 4" maximum depth

Size: Size is based on drainage area and soil type. Gardens with clay soils are shallower, so usually will have larger area. These are guidelines, not absolutes.

Total drainage area (from Step 1):	sq ft
Multiply by factor in table below	
Minimum Size	sq ft

Soil Type	Min Garden Size	Multiply by
A – sandy	5% of drainage area	.05
B- silty loam	8%	.08
C – loamy	10%	.10
D – clay	15%	.15

Step 5: Determine Inlet

Method Materials; Size (length, width, diameter, quantity)
☐ Extended downspout
□ Buried downspout or drain tile
□ Across lawn
□ Vegetated swale
□ Dry creek (rock, no plastic liner)
□ Stone or concrete spillway
□ Other
Erosion Potential Materials and Quantity
□ Velocity and erosion should not be a problem
☐ Erosion possible, address this with: ☐ Grading ☐ Rocks or obstructions to slow flow ☐ Rocks to stabilize ☐ Erosion control blanket

Step 6: Determine Overflow Check all that apply
 Yes, overflow is away from buildings Berm higher near building Over flow sheets over lawn or garden Overflow sheets over driveway, walkway Flows onto street Other
Step 7: Summarize Design
Size:
Depth:
Amendments:
Materials:
Attach project plans:

Construction Methods & Materials

Step 1: Call Gopher One Before digging call Gopher One – 651-454-002, 800-252-1166 Step 2: Mark and Dig Garden How remove soil? Where put excess soil? ☐ Shovel ☐ Use for berm around garden ☐ Mini-backhoe ☐ Use or store elsewhere on site ☐ Other ☐ Haul off site Be sure garden bottom is flat and slopes are gentle. Step 3: Scarify and Add Amendments Scarify bottom 6-12" with: How incorporate amendments Shovel ☐ No amendments ☐ Fork ☐ Turn into soil with shovel ☐ Tiller ☐ Till into soil ☐ Other: ☐ Other: ** Must incorporate, do not create layer AVOID COMPACTING SOIL!! Plan your work for least amount of walking in the garden. Step 4: Edge garden Type of edging ☐ plastic \square metal □ rock ☐ brick ☐ Other: **CALCULATION** for Mulch or Amendments

Area of garden / 1000 x 3.12 x depth of amendment = _____ cubic yards of mulch

inches

Sq ft

Ex: 200 sq ft x 3.12×3 " mulch = 1.9 cu yards

Planting Methods & Materials

	Step 1: Determine Design Elements Style Natives or non-natives?				
	 ☐ Wild ☐ Naturalistic but not too wild ☐ Relatively formal ☐ Formal ☐ Other: 	☐ Natives only ☐ Mix of natives and non-natives ☐ Non-natives and cultivars only			
	What zones will you include?	What types of plants?	7		
	 □ Wet zone For type B, C, D soils must use plants that tolerate saturated soils. For type A (sandy) soils may try wider selection of plants. □ Upland zone □ Optional if garden is shallow. □ Annuals □ Bulbs (upland only) □ Perennials □ Shrubs □ Trees 				
	Maximum height of plants				
	All, 2' ☐ Up to 3' ☐ Up to 5' ☐ Over 5'				
	Step 2: Create design				
	 List plants to use in wet zon List plants to use in upland Will plants be mixed or mas Draw design on paper. 	zone.			
Ī	Step 3: Determine # plants Spacing	# plants needed for 100 sq ft			
	☐ Plugs – 12"-15" spacing	12" spacing – 100 plants			
	☐ 2"-4" pots 15"-18" spacing	16" spacing – 56 plants			
	☐ 6"+ pots depends on species☐ Trees & shrubs – depends on s	pecies 24" spacing – 45 plants			
	= 11000 & pin dob = doponds on s	48" spacing – 23 plants			

Calculation for total number plants: Area of garden / 100 * # plants in chart EX: 150 sq ft garden, plugs at 16" spacing 150 sq ft / 100 * 56 = 84 plants